

200V-G4 SERIES AIR-COOLED MIDMOUNT™

Take performance
to the next level.



LIMITED WARRANTY†

2 YEAR

800 HRS

COMMERCIAL

LIMITED WARRANTY†

4 YEAR

800 HRS

RESIDENTIAL

226V-G4

61

810cc, V-twin, OHV
Vanguard
petrol engine

Mowing speeds up to 14.5 KPH and
2.02 hectares/hr. based on 155 cm cutting width*
For more details visit:
grasshoppermower.com/acres



● Standard deck

OPTIONS

- » Quik-D-Tatch® PowerVac™ Collection Systems
- » Down Discharge™ mulching packages
- » 4X Rear Discharge™ decks
- » Side discharge control kit
- » Foot pedal extension kit for QuikAjust™ DropPin™ height adjustment
- » Speed-Trimming™ heavy-duty anti-scalp roller kit
- » Air Dam kit – for dry, dusty conditions
- » LED work lights – plug-in ready
- » Yellow beacon light
- » Sunshade Canopy – vinyl or aluminum
- » Custom Cordura® weather cover
- » GrassMax™ blade options
- » Heavy-duty, grass-grooming striping kit
- » Wide seat conversion kit
- » Extended levers for taller operators
- » Foldable ROPS with adjustable seat belt
- » Bar tread, low-pressure tires
- » Michelin® X® Tweel® 24 x 12-12 Airless Turf Tires
- » Michelin® X® Tweel® 13 x 6.5-6 Airless Tail Wheels
- » Edge-EZE™ edger
- » String Trimmer Mount Kit
- » DuraFlex™ suspension forks



Optional DuraFlex™
Suspension Fork

Enjoy comfort, performance and durability with a compact 200V Series mower. An ergonomic design and integrated, multi-point suspension, coupled with the industry's most comfortable seat, lets you stay comfortably in control – even at faster mowing speeds. A higher horsepower combined with a compact wheelbase provides a great power-to-size ratio.

DURABILITY & LONGEVITY

The Model 226V-G4 is powered by an 810 cc Vanguard V-twin engine. This model features the G4 Hydro-Gear ZT-4400 transmission, which has a self-contained, heavy-duty commercial transaxle that provides powerful, smooth response. Integrated cooling fans and 3.5 cm axles extend service life, and best-in-class transmission fluid change intervals reduce costs and maintenance time. Grasshopper's intelligent design transfers more power to the cutting deck to maintain optimum blade tip speed and enhance cut quality.

Only two Access-Eze™ lubrication points cut maintenance time up to 95%.

MANICURED CUT

14 cm-deep decks designed for exceptional durability easily convert from wide-pattern side discharge to optional mulching or vacuum collection. The QuikAjust™ DropPin™ Height Adjustment makes cutting height change fast and simple. Optional four-spindle 4XRD dedicated rear-discharge decks evenly distribute clippings under the mower and out back for a smooth cut and no windrowing.

COMFORT & ERGONOMICS

The deep-cushioned, deluxe Premium Comfort seat features a coil-spring suspension and padded lumbar support with sliding 5 cm fore and aft adjustment for all-day comfort. Iso-mounting eliminates vibration even before it reaches the seat, and both padded seat and foldable armrests are covered in scuff-resistant, breathable CoolTemp Cordura® fabric, which dissipates heat and won't tear or crack with extended use.

QuikAjust Tilt™ steering levers with “no tools” adjustment provide a 23 cm range for maximum comfort and fit.

The 6.5 gal/24.6L single-fill fuel tank under the seat lowers the center of gravity of the machine, providing traction and stability for an enhanced ride. Standard bumper protects the rear of the mower while preserving easy access and removal of the service shield.

MODEL – CUTTING WIDTH	● Standard ○ Option	226V-G4 61
ENGINE		
Type/Displacement/Cylinders		
Vanguard – gasoline/49.4 cu. in. (810 cc)/v-twin		
Lubrication System		
Pressure Lube, Filter		
Crankshaft / Cooling System		
Vertical / Air		
Fuel / Capacity		
Gasoline - unleaded / 6.5 U.S. Gal (24.6 L)		
Air Cleaner		
Remote-mounted, centrifugal multi-stage air cleaner with advanced debris management		
Muffler		
Ultra-quiet, single, industrial type		
DECKS – Side Discharge or Dedicated 4X Rear Discharge (4XRD)		
Construction (Robotic-welded steel)		
Double-layered 10-gauge plus 10-gauge formed-steel spindle plane 0.269 in. (6.83 mm) thick with 7-gauge skirts Spindle plane is 0.9 in. (22.86 mm) thick in stress zones; anvil-edge design with 0.5 in. (12.7 mm) reinforcement on front edge of deck (See Page 8 for thickness diagram)		
Blades (MARBAIN®, 1/4-in.)		
(3) 21 in. (53.3 cm)		
Spindle Assemblies		
Turned, ground and polished 2.5 cm (approx. 1 in.) outside diameter (O.D.) precision shaft; spindle head designed to eliminate fiber wrap; double bearings, non-greasable		
Spindle Housing		
8-in. (20.3 cm)-diameter machined aluminum housing with 6-bolt pattern		
Spindle Cones		
Spindle cones shield housing and lower bearings from fiber wrap and dirt ingestion		
QuikAdjust™ DropPin™ Height Adjustment		
Foot-controlled height adjustment pedal with pin		
Cutting Height Range		
1.0 – 4.5 in. (2.5 – 11.4 cm) in 1/4-inch increments		
Blade Drive		
Belt drive with single Kevlar V-belt & idler arm tensioning		
DEDICATED 4X REAR DISCHARGE DECK OPTION - Additional Information		
4th Spindle and Grass Thrower Blade		
Cast iron thrower spindle housing – 5-in. (12.7 cm) -diameter with 4-bolt pattern		
(1) 18 in. High-Low Mulching Grass Thrower Blade		
STARTER & ELECTRICAL SYSTEM		
Maintenance-Free Battery/Charging Capacity/Starter		
12 Volt/16 amp/solenoid shift		
Ignition		
Breakerless		
Interlock System		
Prevents engine start when PTO clutch is engaged or steering levers are in drive position; allows operator dismount without engine shutdown only when PTO is disengaged and steering levers are locked in neutral		
ULTIMATE OPERATOR STATION™		
Premium Comfort Seat		
Iso-mounted, high-back, deep-cushioned, foam-padded Cordura®-covered, padded foldable arms, padded backrest with lumbar support, coil-spring suspension and embroidered Grasshopper logo on seat back; adjustable fore and aft		
Operator Protection		
Rollover Protection Structure (ROPS) with seat belt		
Suspension		
Roomy, iso-mounted footrest with Shock Impact Reduction System™ (SIRS™)		
Console-Mounted Instruments		
Low engine oil pressure, digital hour meter, parking brake indicator light, ignition switch and push/pull PTO switch. Choke integrated with throttle lever.		
Work Lights (Pre-wired)		
LED (optional)		

MODEL – CUTTING WIDTH	226V-G4 61
TRANSMISSION & STEERING	
Type	
Heavy-duty Hydro-Gear ZT-4400 hydrostatic transmissions with cooling fans; integrated transaxles with 12 cc piston pumps and 16 cc piston motors, gear reduction, internal disc brakes, and 1-3/8 inch axles	
Filtration/Hydro Fluid	
Self-contained fluid and internal filtration / CoolTemp Hydro-Max™ fluid withstands high and low temperature extremes for extended service intervals after 100-hour break in oil change	
Speed	
0 – 9.0 mph (0 – 14.5 kph) forward 0 – 6.0 mph (0 – 9.7 kph) reverse	
Turning Radius	
True zero degree, turns within own length with counter-rotating, independently powered drive wheels	
Steering	
One- or two-handed operation with QuikAdjust Tilt™ dual levers with 9-inch comfort range that automatically return to neutral from either forward or reverse position	
Brakes	
Dynamic braking through hydrostatic transmission	
Parking Brake	
Internal disc brake in transmission	
TIRE SIZES	
Drive Wheels – Standard (5-bolt pattern)	
24 x 12-12 turf type, 4-ply rated	●
24 x 12-12 bar tread, 4-ply rated	○
24 x 12-12 Airless Turf Tweel Drive Wheel	○
Front Casters	
13 x 6.5-6 rib tread, pneumatic with double-sealed bearings	
DIMENSIONS (Mower & Deck)	
Mulch Width/Length (Add 1.5 in. (3.8 cm) to width for side discharge with deflector raised. Add 12.0 in. (30.5 cm) to width for side discharge with deflector.) <i>Mulching kit optional.</i>	
62.5 in. (158.8 cm)/79.0 in. (200.7 cm)	
Height (Seat back)	
46.0 in. (116.8 cm)	
Height (Seat cushion)	
30.0 in. (76.2 cm)	
Height (ROPS)	
68.0 in. (172.7 cm)	
Drive Tire Track Width (outside edge to outside edge)	
50.0 in. (127.0 cm)	
WEIGHT	
Uncrated: (Mower & Deck) 1030 lbs. (467.2 kg)	
Mulching Package (Package includes high-low mulching blades.)	
29 lbs. (13.2 kg)	